

HOUSEHOLD DEHUMIDIFIER

Dry Digit 21 LCD

Provided with:

- Electronic Control
- Display LCD
- Elegant and refined design

Peculiarities:

- Two speed fan
- Low Power Consumption
- Color: Ivory white

Used mainly in:

- Houses, Kitchen
- Laundries
- Shops
- Libraries



TECHNICAL DATA:

Rated Maximum Power absorbed (at 20°C, 60% R.H.)	310 W
Rated Maximum Power absorbed (at 35°C, 95% R.H.)	4420 W
Max. Current Absorbed (at 35°C, 95% R.H.)	2 A
Air Flow	250 mc/h
Sound Pressure Level (at 3 mts in free field)	38 db(A)
Refrigerant	R290
Defrosting Control System	elettronic
Capacity of Condensed Water Tank	6 Lt
Functioning Temperature Range	6-35 °C
Functioning Relative Humidity Range	40 - 90 %
Rated Condensation Capacity (at 30°C - 80 %)	21 l/ 24h
Rated Condensation Capacity (at 32°C-90 %)	22 l/ 24h
Weight with empty tank	12,7 kg
Dimensions LxDxH mm	362x270x582
Dimensions with Packaging Carton Boxes LxDxH mm	390x300x625
Number of Units in 40' (20') container	circa 980 (450)
Voltage Available:	230/1/50

CONDENSED HUMIDITY AT DIFFERENT TEMPERATURES AND R.H. CONDITIONS

Room conditions	Condensed Water
10°C - 60%	4 l/24h
10°C - 80%	7 l/24h
15°C - 60%	6 l/24h
15°C - 80%	9 l/24h
20°C - 60%	8 l/24h
20°C - 80%	12 l/24h
25°C - 60%	10 l/24h
25°C - 80%	14 l/24h
27°C - 65%	13 l/24h
27°C - 80%	16 l/24h
30°C - 80%	21 l/24h
32°C - 80%	22 l/24h

Data Sheet DD21 LCD V1011